



**Green Country
Lights LLC**

Parking Light Series

Specifications



Lifespan
50,000hrs



Operating Temperature
-40°C - +40°C



IP65 rating

FEATURES

- High pressure die cast aluminum housing, Anti-static powder coat finish.
- Highly efficient thermal conductive heat dissipation system.
- Slip fitter, U-bracket and straight arm are available.
- High efficient CreeX-TE LED Chip module ensures excellent performance.
- Beautiful appearance, Easy Installation, Maintenance Free.
- IP Rating: IP65

Application

- Parking lots, pedestrian walkways, roadways, and other outdoor applications

CERTIFICATION



Sensor Option



Slip Fitter



Straight Arm



U-Bracket




SPECIFICATIONS

Model	Power	ETL	DLC	Input Voltage	CCT	CRI	Delivered Lumens (5K)	Power Factor	THD	Installation
DG120SB	120W	YES	YES	100-277V 50/60HZ	5000K	>75	10,800 LM	>0.92	<15%	Slip Fitter, U-Bracket or Straight Arms
DG180SB	180W	YES	YES				17,100 LM			
DG300SB	300W	YES	YES				25,000 LM			

DIMENSION



Model	Weight
DG120PL	9.8 Kg
DG180PL	10.8 Kg
DG300PL	11.8 Kg



Inch(mm)

